


# Flanged End Check Class 600

L6-40



			1/2		3/4		1		1 1/2		2	
CONV. PORT	A	End to End	165	6 1/2	191	7 1/2	216	8 1/2	241	9 1/2	292	11 1/2
	B	Center to Top -Open	72	2 5/6	80	3 1/7	85	3 1/3	115	4 1/2	130	5 1/9
	D	Piston Ball	9	0.354	13	0.511	17.5	0.689	29.5	1.161	35	1.377
		Swing	9.6	0.378	14	0.551	17.5	0.689	29.5	1.607	36.6	1.440
	Approximate Wt-Kg		3.5		5.7		8.0		14.5		19.5	
	Approximate Wt-Lbs		7.7		12.54		17.6		31.9		42.9	
FULL PORT	A	End to End	165	6 1/2	191	7 1/2	216	8 1/2	241	9 1/2	292	11 1/2
	B	Center to Top -Open	75	3	90	3 1/2	100	4	120	4 5/7	150	6
	D	Piston Ball	13	0.511	17.5	0.689	22.5	0.885	35	1.377	45	1.770
		Swing	14	0.551	18	0.708	24	0.944	36.6	1.440	48	1.889
	Approximate Wt-Kg		3.8		6.5		8.5		16		23	
	Approximate Wt-Lbs		8.4		14.3		18.7		35.2		50.6	